

PRODUCT SPECIFICATIONS

SLAT DIMENSIONS	Overall standard thickness is 1 9/16" Panels include a ¾" thick nominal veneered backer (11/16") Standard individual slat size is 1" face, 11/16" visible depth
PANEL WIDTH	2' or 4' standard
PANEL HEIGHT	8' standard Up to 10' available (price increase applies, may be subject to longer lead time)
LAYUP	Plain Sawn, Book Matched
MINIMUM	225sf, small batch quantities available
FINISH	Unfinished or Prefinished
INSTALLATION	Typically installed with Z clips

NOTE: Pricing of all wall panel products experience fluctuations. Please reach out for current pricing for your specific project.



TRIBUTARY DIMENSIONAL WOOD WALL & CEILING PANELS

PRODUCT DATA

Description: Three-dimensional wall and ceiling panels with solid wood slats and veneer backer on MDF.

Species Options: Select White Oak, Select Walnut

Source Options: Sustainably Managed Midwest Forests (Select Harvest), FSC® Certified Available on

Request (FSC-C199866)

Dimensions: 4'x8' panels standard

Weight: 2.75-3lbs per SF

Core: 11/16" MDF, NAF, TSCA Title VI Compliant, Class A Fire Rated and/or FSC Certified Core available

on request (FSC-C199866)

Finish Options: All standard finishes are Class A Fire Rated.

Additional Options: Trim and corner pieces available for an additional charge. Unfinished slatted wall panels are available upon request.

Site Conditions: For most installations, we recommend a climatic temperature between 55 to 75 degrees Fahrenheit and 30% to 50% humidity level. Environments that do not meet these criteria will cause wood to experience shrinking and swelling issues that damage the product. We cannot guarantee our product's performance in such environments.

Installation: Installation materials are not included and must be purchased separately. For wall installation, we recommend using MF375 Monarch Z-Clips. For ceiling installations, please contact us for specific fasteners.

Grain and Allowances: Natural color variation will occur across panels. White Oak and Walnut panels may include sapwood up to 10% of total panel. Small, sound pin knots may occur in solid wood slats.

LEED: Urban Evolutions veneer panels may contribute toward satisfying the following credits under LEED® v4.1:

M&R - Material Ingredients - Declare

M&R - Sourcing of Raw Materials - Material Reuse (Urban Wood)

IEQ - Low-Emitting Materials - Formaldehyde Emissions Evaluation (MDF)

Sustainability: Our wood wall panels are Living Building Challenge Red List Free, feature Greenguard Gold finish options, and use Eco-Certified MDF. Please reach out to Emma Kiel at emma@urbanevolutions.com for sustainability inquiries and Matt Rasmussen at matt@urbanevolutions.com for technical specifications.

